


PERFORMANCE DATA-VACUUM											ELECTRIC MOTOR REQUIREMENT								
Model	R.P.M.	Inches Inlet	Hg	5.0	10.0	10.9	13.9	14.8	15.9	18.0	20.0	Hg.	10.0	13.0	14.8	15.0	18.0	20.0	
				kPa	15.9	33.9	37.9	44.9	50.0	50.8	60.9	67.7	kPa	33.9	44.0	50.0	50.8	60.9	67.7
MXLS0ES	R.P.M. Range 950- 1425	1010	65	SCFM	52.5	41.7	38.3	34.6	30.4	30.0	23.4	19.3	Hp	3.0	3.0	3.0	3.0	3.0	3.0
			—	ACFM	63.0	62.6	62.3	61.1	60.0	60.0	58.5	57.9		Kw	2.2	2.2	2.2	2.2	2.2
	Maximum Continuous Vacuum 20" Hg 67.7 kPa	1200	76	SCFM	63.0	49.4	45.3	42.5	37.4	36.9	28.0	23.0	Hp	3.0	3.0	3.0	3.0	5.0	5.0
			—	ACFM	75.6	74.1	74.0	73.9	73.8	73.0	70.0	69.0		Kw	2.2	2.2	2.2	2.2	3.0
	1425	91	SCFM	67.4	86.9	86.7	86.0	85.8	85.8	81.8	81.0	Hp	5.0	5.0	5.0	5.0	5.0	5.0	
		—	ACFM	87.4	86.9	86.7	86.0	85.8	85.8	81.8	81.0		Kw	3.0	3.0	3.0	3.0	3.0	3.0
MXLS0ES	R.P.M. Range 895- 1350	895	113	SCFM	67.5	68.7	63.0	58.6	51.5	50.8	39.5	—	Hp	5.0	5.0	5.0	5.0	5.0	—
			—	ACFM	105.0	103.1	102.5	102.0	101.9	101.6	98.8	—		Kw	4.0	4.0	4.0	4.0	4.0
	Maximum Continuous Vacuum 18" Hg 60.9 kPa	1150	144	SCFM	111.0	87.0	79.8	72.7	63.9	63.0	50.0	—	Hp	5.0	5.0	5.0	5.0	7.5	—
			—	ACFM	133.2	130.5	129.0	127.1	126.0	125.0	125.0	—		Kw	4.0	4.0	4.0	4.0	5.5
	1250	155	SCFM	119.3	93.5	85.8	78.1	68.6	67.7	53.8	—	Hp	7.5	7.5	7.5	7.5	7.5	—	
		—	ACFM	143.2	140.3	138.6	137.4	136.5	135.5	134.4	—		Kw	5.5	5.5	5.5	5.5	5.5	—
MXLT.0ES	R.P.M. Range 950- 1350	950	180	SCFM	137.6	106.8	96.0	89.8	78.9	77.9	58.8	—	Hp	7.5	7.5	7.5	7.5	7.5	—
			—	ACFM	165.1	160.2	159.7	158.4	155.6	155.6	147.0	—		Kw	5.5	5.5	5.5	5.5	7.5
	Maximum Continuous Vacuum 18" Hg 60.9 kPa	1100	209	SCFM	153.6	122.0	112.7	104.8	92.0	90.8	69.4	—	Hp	7.5	7.5	7.5	7.5	10.0	—
			—	ACFM	184.6	184.2	183.3	182.4	181.6	181.6	173.5	—		Kw	7.5	7.5	7.5	7.5	7.5
	1325	251	SCFM	193.2	151.4	138.9	128.7	113.0	111.5	86.6	—	Hp	10.0	10.0	10.0	10.0	10.0	—	
		—	ACFM	231.6	227.1	225.8	224.3	223.0	223.0	216.5	—		Kw	7.5	7.5	7.5	7.5	7.5	—
7108	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	



SHIPPING CASE DATA

Model	Length	Width	Height	Volume	Weight	
MXLS0ES	inches	10 1/2	12 1/4	11 1/4	sf	16
	mm	420	315	285	sf	0.036
MXLS0ES	inches	19 1/4	14	15 1/4	sf	2.40
	mm	486	355	390	sf	0.068
MXLT.0ES	inches	26 1/4	14	15 1/4	sf	3.33
	mm	665	355	390	sf	0.094

DIMENSIONAL DATA

Model	A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T	U
MXLS0ES	inches	6 1/2	14 1/2	3 1/2	2 1/2	2 1/2	4	13 1/2	4 1/2	6 1/2	1 1/2	1 1/2	8 1/2	7	5	7 1/2	6 1/2	8 1/2	15 1/2
	mm	111	368	70	64	64	102	342	114	147	38	38	204	178	127	192	165	200	393
MXLS0ES	inches	7 1/4	14 1/2	3 1/2	3 1/2	3 1/2	3 1/2	15 1/2	6 1/2	7 1/2	1 1/2	2	10 1/2	9 1/2	7 1/2	7 1/2	8 1/2	13 1/2	16 1/2
	mm	182	368	90	90	90	90	396	165	190	38	51	268	244	190	190	216	335	419
MXLT.0ES	inches	9	14 1/2	3 1/2	3 1/2	3 1/2	4 1/2	16 1/2	6 1/2	7 1/2	1 1/2	2	10 1/2	9 1/2	7 1/2	7 1/2	8 1/2	13 1/2	16 1/2
	mm	229	368	90	90	90	110	417	165	190	38	51	268	244	190	190	216	335	419